



Image quality and speed in one affordable package

The EFI™ H652 UV hybrid printer is the perfect choice for high image quality, quick turn wide-format graphics.



Get in the game with UV hybrid printing

- Photographic image quality at production-level speeds for demanding customers
- Four-color plus white ink for spot color and under and overprinting
- Breakthrough vacuum belt media transport system to handle a wide range of flexible and rigid media
- Up to eight levels of variable drop grayscale for near photographic image quality

Ideal Applications:

- Banners
- Display and exhibition graphics
- Flags
- Indoor and outdoor signage
- Industrial–Membrane switch
- Packaging
- Posters
- Point-of-Purchase advertising

Typical Substrates:

- Foam-Cor
- PVC
- Styrene
- Corrugated plastics
- Plywood
- MDO
- Paper
- Aluminium
- Aluminium plastic composite
- Cardboard
- Acrylic
- Glass

Features and benefits

- CMYK plus white
- Up to 455 ft²/hr (42.27 m²/hr)
- Up to 1200 x 600 dpi
- Up to eight levels of grayscale

Media/Handling

- Handles flexible and rigid substrates up to 65 inches (165 cm) wide and 1.8 inches (4.572 cm) thick. Image width 64 inches (162.56 cm)
- Vacuum belt drive system
- Maximum media weight – 75 lbs (34.01kg)
- Maximum roll diameter – 9 inches (22.86 cm)

Resolution

- 300 x 300 dpi eight levels of grayscale
- 600 x 600 dpi four & eight levels of grayscale
- 900 x 900 dpi four & eight levels of grayscale
- 1200 x 600 dpi eight levels of grayscale

Productivity

- Ultra Quality Mode, 16 Pass, 600 dpi, 80 ft²/hr (7.43 m²/hr)
- High Quality Mode, 8 Pass, 600 dpi, 130 ft²/hr (12.1 m²/hr)
- Quality Mode, 4 Pass, 600 dpi, 255 ft²/hr (23.69 m²/hr)
- Draft Mode, 2 Pass, 300 dpi, 455 ft²/hr (42.27 m²/hr)
- White Printing, 1/2 CMYK

Print system

- Five piezoelectric grayscale print heads, up to eight levels of grayscale
- Two shuttered Mercury Lamps with high and low power settings
- One-year printer warranty (excluding consumables)

Formats

- All popular desktop files formats, including PostScript®3™, EPS, TIFF, PDF and RGB/CMYK

Genuine EFI inks

- Inks are supplied in 1-liter bottles available in cyan, magenta, yellow, black and white
- Ships with 210C flexible ink set for standard printing applications

Environmental considerations

- Temperature: 65° F to 80° F (18° C to 26.7° C)
- Humidity: 20% to 80% (non-condensing)
- Weight: 1000.0 lbs. (635.029 kg)
- Height: 52 inches (132.08 cm)
- Width: 121.5 inches (308.61 cm)
- Depth: 40 inches (101.06 cm) without tables
- Depth: 94 inches (238.76) with tables
- Electrical: 205-234VAC, Single Phase, 50/60Hz, 16 Amps average running; 30 Amp peak supply

EFI Fiery XF digital front end

- Optimised for use with the EFI Fiery XF RIP
- Bi-directional communication capability between the Fiery XF RIP and EFI Wide Format printer allows back communication of audit information on every print job
- Advanced, easy-to-use, wizard-guided color tools for consistent, predictable, high-quality color
- Powerful production tools like nesting, step and repeat, scaling, cropping, and tiling
- Advanced ICC color management for reliable color, quality output and proofing-quality color
- Scalable, versatile platform grows with your needs as your business grows
- Three-day, on-site EFI Fiery XF Color & Workflow training available

EFI fuels success.

From Fiery to superwide inkjet, from the lowest cost per label to the most automated business processes, EFI has everything your company needs to succeed. Visit www.efi.com or call 650-357-3500 for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, Best, the Best logo, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, DockNet, Digital StoreFront, DocBuilder, DocBuilder Pro, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPPhoto, EPRRegister, EPStatus, Estimate, ExpressPay, Fabrivu, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, Inkintensity, Inkware, Jetrion, the Jetrion logo, LapNet, Logic, MiniNet, Monarch, MicroPress, OneFlow, Pace, PhotoXposure, Printcafe, PressVu, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, Printstream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Rastek, the Rastek logo, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEK, the VUTEK logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.